

Torque adjustment.



3.Servo Motor:

Provide Fast forward-Reverse rotation and good and steady torque.





2.Upper Arm:

It consists of gas spring which make the machine floating and nullify the vertical load acting on tap.








Standard Arm
Vertical Head Machine
(Order Code 'SV')



Standard Arm Universal Head Machine (Order Code 'SU')



Model	Capacity	Working Radius Std Arm	Speed	Power	Tap collets
TAP SMART - 12	M3-M12	1200mm	0-600Rpm	800W	M3,4,5,6,8,10,12
TAP SMART - 16	M3-M16	1200mm	0-300Rpm	800W	M3,4,5,6,8,10,12,14,16
TAP SMART - 24	M6-M24	1350mm	0-200Rpm	1200W	M6,8,10,12,14,16,20,22,24
TAP SMART - 30	M6-M30	1350mm	0-150Rpm	1200W	M6,8,10,12,14,16,20,22,24,30
TAP SMART - 36	M6-M36	1350mm	0-100Rpm	1200 & 2400W	M6,8,10,12,14,16,20,22,24,30,33,36



Optional Accessories



Working Table:
900x600x700.
Designed with heavy
duty box section frame
and 12mm thick
machined top surface.
Powder coated with
arrangement of castor
mounting.



Quick Change Safety Tap Holder: Torque slip clutch collets ensure controlled torque while tapping and avoid tap breakage.



Magnetic Base: 250x100x190mm Lifting capacity 300/500/1000Kg For easy mounting of machine on large plates and heavy jobs.

Tapping Torque Requirement

Tap Tap Size Collet size		Torque (Nm)
МЗ	3.15 X 2.5	0.5
M4	4 X 3.15	1.4
M5	5 X 4	2.5
M6	6.3 X 5	4.5

Tap Size	Tap Collet size	Torque (Nm)
M8	6.3 X 5	8.5
M10	8 X 6.3	18.0
M12	9 X 7.1	28.0
M14	11.2 X 9	40.0

Tap Size	Tap Collet size	Torque (Nm)
M16	12.5 X 10	50.0
M20	14 X 11.2	86.0
M22	16 X 12.5	100.0
M24	18 X 14	150.0

Tap Size	Tap Collet size	Torque (Nm)
M27	20 X 16	170.0
M30	20 X 16	250.0
M33	22.4 X 18	290.0
M36	25 X 20	400.0



Reg.Office:1392 Shukrawar peth Bajirao Rd Pune 411002

Branch Office: "Raje Manor" Apartment, B1/B2 Sr.No.1,CTS No. 694 Karvenagar, Pune 411052.

Works: S No 31/2/2 Hingne Khurda. Near Rokdoba Mandir. Sinhagad Rd. Vitthawadi Pune 411051.

Contact: +91 09850094773

Mail: ravisonscorporation@gmail.com

Web: www.ravisons.com

Authorised Distributor